



## LEVEL WOUND COIL

Used in air-conditioners, heat exchangers and freezers.  
In conformity with ASTM B68 (USA) and JIS H3300 (Japan).

Outer Diameter		Wall Thickness (mm)											
mm	inch	0.27	0.31	0.35	0.41	0.51	0.56	0.61	0.71	0.81	0.91	1.00	1.20
4.00					●	●	●	●	●	●			
4.76	3/16"				●	●	●	●	●	●			
6.00					●	●	●	●	●	●			
6.35	1/4"	●	●	●	●	●	●	●	●	●	●	●	●
7.00		●	●	●	●	●	●	●	●	●	●	●	●
7.94	5/16"	●	●	●	●	●	●	●	●	●	●	●	●
9.52	3/8"	●	●	●	●	●	●	●	●	●	●	●	●
10.00					●	●	●	●	●	●	●	●	●
12.00					●	●	●	●	●	●	●	●	●
12.70	1/2"		●	●	●	●	●	●	●	●	●	●	●
15.00					●	●	●	●	●	●	●	●	●
15.88	5/8"				●	●	●	●	●	●	●	●	●
19.05	3/4"							●	●	●	●	●	●
22.22	7/8"								●	●	●	●	●
25.40	1"								●	●	●	●	●
28.58	1 1/8"								●	●	●	●	●